
# **BOLTHOLD** EPX2 Datasheet v3.5

**BoltHold** is a family of anchors specifically designed for anchoring to asphalt surfaces. The anchors require the use of grout to bind the anchors to the asphalt without stress.



#### **Description**

The EPX2 is a tested and proven grout, offered for sale by Asphalt Anchors Corp. It is a cement-based anchoring cement which expands as it cures, to fill crevices in the asphalt. The material is resistant to immersion in water once it is fully cured.

This grout should not be used with our Dacromet coated anchors, as it contains certain additives that tend to attack the coating over time. Use 2-part epoxies for Dacromet anchors.

**Setting time** 10 minutes mixture working time. Allow 2 hours for a set of 2000 psi. The grout will further harden over time, but at 2,000 psi it is already stronger than the asphalt it bonds with.

## **Shelf Life**

When kept in dry and cool environment, shelf life is over 5 years.

## Fire Rating

Contains no combustible materials.

## <u>Mixing</u>

The EPX2 is provided as a dry powder. It requires water to activate. The mix re-

quires **approximately** 4oz of water by weight to 12 oz of EPX2 powder by weight. See Anchor installation manual for details and the correct mixing procedure.

Note that some find it easier to add the powder to water rather than water to the powder.

## **Packaging**

The EPX2 is available in 12 oz. bags and in 10 lb. tubs. The bags are packaged in a 6-pack carton, and are not available as individual bags.



<u>Yield</u>: The EPX2 12 oz bag cures into 250 mL mix. One **bag** is enough for 3 SP10, or 1.5 SP12, or 1.2 SP18, or 0.6 SP58 anchors. One **tub** is enough for 45 SP10, 22 SP12, 16 SP18, or 10 SP58.

## Warning

The powder is not considered hazardous, but it is caustic once mixed with water. Wear eye protection when dealing with the powder. Avoid direct contact with eyes or skin.

See Safety Data Sheet for details.

	6-Bags	tub
Weight	5.5 lb.	10 lb.
Dimensions	6 x 8 x 4"	6x6x6"
SKU	82-5002.K	82-5002.010



10 Ridge Rd, West Orange, NJ 07052 USA

**Tel**: 1.973.669.8214 **Fax**: 1.973.669.5161

**email**: marketing@asphaltanchors.com **WEB**: www.asphaltanchors.com