


BOLTHOLD™ EPX2 Datasheet v3.5

BoltHold is a family of anchors specifically designed for anchoring to asphalt surfaces. The anchors require the use of grout to bind the anchors to the asphalt without stress.



weight to 12 oz of EPX2 powder by weight. See [Anchor installation manual](#) for details and the correct mixing procedure.

Temperature Range

You can apply the EPX2 at temperatures as low as 40-45 degrees. Use warm water and warm anchors when working at lower temperature. Do not apply at freezing temperatures.

Description

The EPX2 is a tested and proven grout, offered for sale by Asphalt Anchors Corp. It is a cement-based anchoring cement which expands as it cures, to fill crevices in the asphalt. The material is resistant to immersion in water once it is fully cured.

This grout should not be used with our Dacromet coated anchors, as it contains certain additives that tend to attack the coating over time. Use 2-part epoxies for Dacromet anchors.

Setting time 10 minutes mixture working time. Allow 2 hours for a set of 2000 psi. The grout will further harden over time, but at 2,000 psi it is already stronger than the asphalt it bonds with.

Shelf Life

When kept in dry and cool environment, shelf life is over 2 years.

Fire Rating

Contains no combustible materials.

Mixing

The EPX2 is provided as a dry powder. It requires water to activate. The mix requires **approximately** 4oz of water by

Packaging

The EPX2 is available in 12 oz. bags and in 10 lb. tubs. The bags are packaged in a 6-pack carton, and are not available as individual bags.



Yield: The EPX2 12 oz bag cures into 250 mL mix. One **bag** is enough for 3 SP10, or 1.5 SP12, or 1.2 SP18, or 0.6 SP58 anchors. One **tub** is enough for 45 SP10, 22 SP12, 16 SP18, or 10 SP58.

Warning

The powder is not considered hazardous, but it is caustic once mixed with water. Wear eye protection when dealing with the powder. Avoid direct contact with eyes or skin.

	6-Bags	tub
Weight	5.5 lb.	10 lb.
Dimensions	6 x 8 x 4"	6x6x6"
SKU	82-5002.K	82-5002.010

See [Safety Data Sheet](#) for details.



10 Ridge Rd, West Orange, NJ 07052 USA
Tel: 1.973.669.8214
Fax: 1.973.669.5161
email: marketing@asphaltanchors.com
WEB: www.asphaltanchors.com